# QUICKSCAN™ LITE QW2100

## **ODATALOGIC**





#### **MULTI-PURPOSE USES FOR DIFFERENT APPLICATIONS**

The QuickScan™ Lite QW2100 linear imager is an entry level product created specifically for reading long and truncated bar codes which is common in some areas of the world. It is perfect for use in retail, light manufacturing, document/bill processing and banking/ finance environments.

The QW2100 imager is small, lightweight and its ergonomic design is comfortable to use during daily operations. It offers snappy reading performance on most 1D bar codes and features a wide scanning angle with an extended scanning line which is perfect for capturing longer and wider bar codes typically found on utility bills and used by manufacturers of electronic parts. Additionally, the scanning line is thinner and brighter, allowing users to scan at wide angles without having to increase the scanning distance.

The QW2100 imager is available with two interface options: USB or Keyboard Wedge / RS-232 and includes various packaging options so that it can be ordered as a scanner only or as a kit equipped with a scanner, cable and stand to facilitate hands-free reading options.

#### **VERSATILE STAND**

A specially designed stand has been created for the QW2100 imager which is light in weight, collapsible to use as a holder instead of a stand, and also has a 'tiltable head' for various angle settings.













#### **FEATURES**

- Wide scan angle
- Laser-like thinner and extended scan line
- Datalogic's patented 'Green Spot' technology for good-read feedback
- Two interface options: USB or Keyboard Wedge /
- Built with over molded rubber to protect the imager when dropped
- Compact and multi-position stand
- Water and Particulate Sealing Rating: IP42
- Drop Resistance to 1.5 m / 5.0 ft
- Uses the same cables and power supplies as the current QuickScan products
- Bulk packaging available (10 scanners per box)
- USB Certified Kits available
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

### INDUSTRY-APPLICATIONS

- Retail
- Light Manufacturing
- Document / Bill Processing
- Banking / Financial Environments

# QUICKSCAN™ LITE QW2100

## **ODATALOGIC**

#### **DECODING CAPABILITY**

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes. 1D / LINEAR CODES POSTAL CODES Australian Post; British Post; Canadian Post; China Post; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC) STACKED CODES

EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

### **ELECTRICAL**

**CURRENT** Operating (Typical): 340 mA @ 5 VDC Standby/Idle (Typical): 190 mA @ 5 VDC INPUT VOLTAGE 5 VDC +/- 0.5 V

#### **ENVIRONMENTAL**

AMBIENT LIGHT 100,000 lux DROP RESISTANCE Withstands repeated drops from 1.5 m / 5.0 ft

onto a concrete surface ESD PROTECTION (AIR DISCHARGE) 16 kV **HUMIDITY (NON-CONDENSING)** 5 - 95% PARTICULATE AND WATER SEALING IP42

**TEMPERATURE** Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

#### **INTERFACES**

QW2170-BK: RS-232 / Keyboard Wedge INTERFACES OW2120-BK: USB

#### PHYSICAL CHARACTERISTICS

COLORS AVAILABLE **Black** 

**DIMENSIONS** 17.0 x 6.5 x 7.0 cm / 6.7 x 2.5 x 2.7 in

WEIGHT 119.0 g / 4.2 oz

#### READING PERFORMANCE

LIGHT SOURCE Red LED 610-650 nm PRINT CONTRAST RATIO (MINIMUM) 25% READ RATE (MAXIMUM) 400 reads/sec

READING ANGLE Pitch: +/- 65°; Roll (Tilt): +/- 45°; Skew (Yaw):+/- 70°

READING INDICATORS Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED; Good

RESOLUTION (MAXIMUM) 0.102 mm / 4 mils (1D Codes)

FIELD OF VIEW

#### **READING RANGES**

TYPICAL DEPTH OF FIELD Minimum distance determined by symbol length

and scan angle

Printing resolution, contrast, and ambient light

dependent.

5 mils : 2.5 to 15.0 cm / 1.0 to 6.0 in 7.5 mils : 0 to 24.0 cm / 0 to 9.4 in 10 mils: 0 to 35.0 cm / 0 to 13.8 in 13 mils: 0 to 40.0 cm / 0 to 15.7 in 20 mils: 0 to 60.0 cm / 0 to 23.6 in

#### **SAFETY & REGULATORY**

AGENCY APPROVALS The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can

ENVIRONMENTAL COMPLIANCE

be referred to for a list of certifications Complies to China RoHS; Complies to EU RoHS

Datalogic Aladdin configuration program is

#### UTILITIES

DATALOGIC ALADDIN™

available for download at no charge. OPOS / JAVAPOS JavaPOS Utilities are available for download at no

OPOS Utilities are available for download at not charge.

#### WARRANTY

WARRANTY 3-Year Factory Warranty

#### Mounts/Stands

STD-QW20-BK Holder/Stand, Black



